


#### Specifications 规格

Nominal Voltage 额定电压	12V	
Rated Capacity(20 hour rate) 20小时率额定容量	1.3AH	
尺寸 Dimensions ±1mm	Length 长度	97mm(3.81")
	Width 宽度	43.5mm(1.71")
	Height 高度	53mm(2.08")
	Total Height (with terminals) 总高 含端子	58mm(2.28")
Weight 重量	Approx.0.57kg (1.26lbs)	
Standard Terminal 标准端子	F1	

#### 放电特性 Discharge Characteristics(20°C, 68°F)



#### Electrical Specifications 电性能

容量 Capacity 77°F(25°C)	20 hour rate (65mA) 20小时率	1.3AH
	10 hour rate (120mA) 10小时率	1.2AH
	5 hour rate (220mA) 5小时率	1.1AH
	1 hour rate (700mA) 1小时率	0.78AH
Internal Resistance 内阻	Fully charged battery 充足电 77°F(25°C)	110m Ω
Capacity 容量	温度 104°F(40°C)	102%
Affected by 受影响	77°F(25°C)	100%
Temperature 影响	32°F(0°C)	85%
(20 hour rate) 20小时率	5°F(-15°C)	65%
自放电 Self-Discharge 77°F(25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
Charge Constant (恒压) Voltage	循环使用, 首次充电电流低于0.36A 电压14.4-15.0V77°F(25°C) 浮充使用, 电压13.5-13.8V77°F(25°C) Cycle, Initial Charging Current less than 0.36A Voltage 14.4-15.0V77°F(25°C) Standby, Voltage 13.5-13.8V77°F(25°C)	

#### 放电特性 Discharge Characteristics(0°C/32°F, 40°C/104°F)

